CONTENTS

Page

FIGURES vii

TABLES xi

EXECUTIVE SUMMARY xiii

ABSTRACT 1

1. INTRODUCTION 1

2. MEASUREMENT SYSTEM 2

3. SURVEY LOCALE, ANTENNAS AND DRIVE ROUTES 2

3.1 Transmitter Site, Antennas and Drive Routes 2
3.2 Receiver Antennas 4

4. DATA PROCESSING 8

4.1 Basic Transmission Loss 8
4.2 Delay Spread 9

5. RESULTS 10

5.1 Data Overview 10
5.2 Basic Transmission Loss 13
5.3 Basic Transmission Loss Slope 13
5.4 Lognormal Statistics 18
5.5 Delay Statistics 20

6. CONCLUSIONS 22

7. ACKNOWLEDGMENTS 23

8. REFERENCES 24

APPENDIX A: DATA FILE SUMMARY 25

APPENDIX B: FIGURES 26

FIGURES

Page

Figure 1. Transmitter site looking SE along Speer Boulevard. 3

Figure 2. View from the transmitter site looking east towards downtown Denver. 4

Figure 3. View along Speer Boulevard south from the transmitter site..... 5

Figure 4. View of downtown Denver looking east from the transmitter site. 5

Figure 5. Drive route map for radiowave propagation survey in downtown Denver, CO. 6

Figure 6. The measurement van, ground plane and receiving antennas. 6

Figure 7. Basic transmission loss (L_b) at 430 MHz all routes for downtown Denver, CO. 11

Figure 8. Basic transmission loss (L_b) at 1350 MHz all routes for downtown Denver, CO. 11

Figure 9. Basic transmission loss (L_b) at 2260 MHz all routes for downtown Denver, CO. 12

Figure 10. Basic transmission loss (L_b) at 5750 MHz all routes for downtown Denver, CO. 12

Figure 11. Basic transmission loss versus distance, sector 1 route 1, at 430 MHz..... 15

Figure 12. Basic transmission loss versus distance, sector 1 route 1, at 1350 MHz..... 15

Figure 13. Basic transmission loss versus distance, sector 1 route 1, at 2260 MHz..... 16

Figure 14. Basic transmission loss versus distance, sector 1 route 1, at 5750 MHz..... 16

Figure 15. L_b slope versus frequency for three urban drive routes in Denver, CO. 17

Figure 16. Basic transmission loss distribution about the local mean plotted on lognormal paper for the urban high-rise (S2R1) environment in downtown Denver, CO. Data for four frequencies are plotted: (a) 5750 MHz, (b) 2260 MHz, (c) 1350 MHz, and (d) 430 MHz. 19

Figure 17. Basic transmission loss distribution about the local mean plotted on lognormal paper for an urban low-rise (S1R1) environment near downtown Denver, CO. Data for four frequencies are plotted: (a) 5750 MHz, (b) 2260 MHz, (c) 1350 MHz, and (d) 430 MHz. 19

Figure 18. Cumulative distribution of delay spreads, sector 1 route 1, 430-5750 MHz. 20

Figure 19. Median delay spreads versus frequency for each sector and route. 22

Figure B1. Measured delay spread (*S*) at 430 MHz all routes for downtown Denver, CO. 26

Figure B2. Measured delay spread (*S*) at 1350 MHz all routes for downtown Denver, CO. 26

Figure B3. Measured delay spread (*S*) at 2260 MHz all routes for downtown Denver, CO. 27

Figure B4. Measured delay spread (*S*) at 5750 MHz all routes for downtown Denver, CO. 27

Figure B5. Basic transmission loss versus distance, sector 1 route 1, at 430 MHz. 28

Figure B6. Basic transmission loss versus distance, sector 1 route 1, at 1350 MHz. 28

Figure B7. Basic transmission loss versus distance, sector 1 route 1, at 2260 MHz. 29

Figure B8. Basic transmission loss versus distance, sector 1 route 1, at 5750 MHz. 29

Figure B9. Basic transmission loss versus distance, sector 1 route 2, mixed urban low-rise and urban high-rise, at 430 MHz. 30

Figure B10. Basic transmission loss versus distance, sector 1 route 2, mixed urban low-rise and urban high-rise, at 1350 MHz. 30

Figure B11. Basic transmission loss versus distance, sector 1 route 2, mixed urban low-rise and urban high-rise, at 2260 MHz. 31

Figure B12. Basic transmission loss versus distance, sector 1 route 2, mixed urban low-rise and urban high-rise, at 5750 MHz. 31

Figure B13. Basic transmission loss versus distance, sector 1 route 2, urban, at 430 MHz. 32

Figure B14. Basic transmission loss versus distance, sector 1 route 2, urban, at 1350 MHz. 32

Figure B15. Basic transmission loss versus distance, sector 1 route 2, urban, at 2260 MHz. 33

Figure B16. Basic transmission loss versus distance, sector 1 route 2, urban, at 5750 MHz. 33

Figure B17. Basic transmission loss versus distance, sector 1 route 2, urban mixed, at 430 MHz. 34

Figure B18. Basic transmission loss versus distance, sector 1 route 2, urban mixed, at 1350 MHz. 34

Figure B19. Basic transmission loss versus distance, sector 1 route 2, urban mixed, at 2260 MHz. 35

Figure B20. Basic transmission loss versus distance, sector 1 route 2, urban mixed, at 5750 MHz. 35

Figure B21. Basic transmission loss versus distance, sector 2 route1, urban high-rise, 430 MHz. 36

Figure B22. Basic transmission loss versus distance, sector 2 route 1, urban high-rise, 1350 MHz. 36

Figure B23. Basic transmission loss versus distance, sector 2 route1, urban high-rise, 2260 MHz. 37

Figure B24. Basic transmission loss versus distance, sector 2 route1, urban high-rise, 5750 MHz. 37

Figure B25. Cumulative distribution of delay spreads, sector 1 route 2, 430-5750 MHz. 38

Figure B26. Cumulative distribution of delay spreads, sector 2 route 1, 430-5750 MHz. 38

Figure B27. Cumulative distribution of the maximum delay, sector 1 route 1. 39

Figure B28. Cumulative distribution of the maximum delay, sector 1 route 2. 39

Figure B29. Cumulative distribution of the maximum delay, sector 2 route 1. 40

Figure B30. Delay spread not exceeded 90% of the time versus frequency for all drive routes. 40

TABLES

Page

Table 1. Transmitter Site Coordinates and Antenna Boresight Directions 7

Table 2. Transmit Antenna Specifications 7

Table 3. Receive Antenna Specifications 7

Table 4. The Power at Antenna Terminals and EIRP Transmitted versus Frequency 7

Table 5. L_b Slopes for Three Routes in the Downtown Area of Denver, CO 18

Table 6. Summary of Attenuation Slopes for Three Routes in the Downtown Area of Denver, CO 18

Table 7. L_b Slopes Measured at 1850 MHz in an Urban Area of Southern England and Predictions Made Using the Hata Model 18

Table 8. Delay Spread Cumulative Distribution Summary at 50% and 10% Quantiles by Drive Routes with Averages 21

Table 9. Maximum Delay Cumulative Distribution Summary at 50% and 10% Quantiles by Drive Route with Averages 21

Table A1. Raw Data File Information 25