

MAN-MADE RADIO NOISE

PART I: ESTIMATES FOR BUSINESS, RESIDENTIAL, AND RURAL AREAS

A. D. SPAULDING
R. T. DISNEY



U.S. DEPARTMENT OF COMMERCE
Frederick B. Dent, Secretary

Betsy Ancker-Johnson, Ph. D.
Assistant Secretary for Science and Technology

OFFICE OF TELECOMMUNICATIONS
John M. Richardson, Acting Director

JUNE 1974



**UNITED STATES DEPARTMENT OF COMMERCE
OFFICE OF TELECOMMUNICATIONS
STATEMENT OF MISSION**

The mission of the Office of Telecommunications in the Department of Commerce is to assist the Department in fostering, serving, and promoting the nation's economic development and technological advancement by improving man's comprehension of telecommunication science and by assuring effective use and growth of the nation's telecommunication resources.

In carrying out this mission, the Office

- Performs analysis, engineering, and related administrative functions responsive to the needs of the Director of the Office of Telecommunications Policy, Executive Office of the President, in the performance of his responsibilities for the management of the radio spectrum
- Conducts research needed in the evaluation and development of telecommunication policy as required by the Office of Telecommunications Policy, pursuant to Executive Order 11556
- Conducts research needed in the evaluation and development of other policy as required by the Department of Commerce
- Assists other government agencies in the use of telecommunications
- Conducts research, engineering, and analysis in the general field of telecommunication science to meet government needs
- Acquires, analyzes, synthesizes, and disseminates information for the efficient use of the nation's telecommunication resources.

TABLE OF CONTENTS

	Page
LIST OF FIGURES	v
LIST OF TABLES	xi
ABSTRACT	1
1. INTRODUCTION	2
2. NOISE PARAMETERS	3
3. ESTIMATION METHODS AND THE DATA BASE	8
4. MAN-MADE RADIO NOISE ESTIMATES	12
4.1 Available Noise Power, F_a	12
4.1.1 Estimates of F_a for Typical Areas	13
4.1.2 Power Lines	36
4.2 The Average and Logarithmic Moments, V_d and L_d	44
4.3 Amplitude and Time Statistics	63
5. USE OF THE MAN-MADE NOISE ESTIMATES IN DETERMINING SYSTEM PERFORMANCE	86
6. MATHEMATICAL MODELING OF THE NOISE PROCESS	90
7. CONCLUSIONS AND DISCUSSION	93
8. ACKNOWLEDGMENTS	97
9. REFERENCES	99
APPENDIX A. MEASUREMENT METHODS USED TO OBTAIN THE DATA BASE	A1
REFERENCES, APPENDIX A	A12
APPENDIX B. THE USE OF TRAFFIC DENSITY INFORMATION AS A NOISE PREDICTOR	B1
REFERENCES, APPENDIX B	B11

LIST OF FIGURES

	Page
Figure 1. Estimates of median values of man-made noise expected at typical locations.	23
Figure 2. Distribution of location median values of man-made noise, 20 MHz residential area data.	24
Figure 3. Distribution of F_a values for a given location.	25
Figure 4. Expected variation of man-made radio noise levels at a location within an hour.	26
Figure 5. Estimates of man-made noise levels and their variation within an hour for business areas.	27
Figure 6. Estimates of man-made noise levels and their variation within an hour for residential areas.	28
Figure 7. Estimates of man-made noise levels and their variation within an hour for rural areas.	29
Figure 8. Estimates of man-made noise levels and their variation within an hour for interstate highways.	30
Figure 9. Estimates of man-made noise levels and their variation within an hour for parks and university campuses.	31
Figure 10. Radio-noise measurements, Dept. of Commerce Boulder Labs, end of Wing 1.	32
Figure 11. Radio-noise measurements, Dept. of Commerce Boulder Labs, end of Wing 1.	33
Figure 12. Hourly median values of radio noise, measured near highway in front of Dept. of Commerce Boulder Labs, October 25-28, 1967.	34
Figure 13. Horizontal versus vertical component of man-made radio noise at 250 MHz.	35

Figure 14. Decrease in power line noise with distance at 0.5 MHz.	39
Figure 15. Decrease in power line noise with distance at 102 MHz.	40
Figure 16. Power line noise measurements taken moving parallel to a 115 kV line in rural Wymoing, both under the line and 1/4 mile from the line.	41
Figure 17. Expected decrease of radio noise radiated from 115 kV H-frame power line with distance from line.	42
Figure 18. Expected radio noise power, F^a , and its standard deviation, σ_{F^a} , from 115 kV, H-frame power transmission line. Receiving antenna under and 0.01 mi. (16.09 meters) from power line.	43
Figure 19. Mean of location median values of V_d , values measured in a 4-kHz bandwidth.	49
Figure 20. Mean of location median values of L_d , values measured in a 4-kHz bandwidth.	50
Figure 21. Mean of location median values of V_d , values measured in a 10-kHz bandwidth.	51
Figure 22. Mean of location median values of L_d , values measured in a 10-kHz bandwidth.	52
Figure 23. Expected median values of V_d and L_d for business areas.	53
Figure 24. Expected median values of V_d and L_d for residential areas.	54
Figure 25. Expected median values of V_d and L_d for rural areas.	55
Figure 26. Distribution of V_d within an hour for a residential area.	56
Figure 27. Distribution of L_d within an hour for a residential area.	57

Figure 28. Median values of V_d measured along interstate highways, in parks, and on university campuses.	58
Figure 29. Median values of L_d measured along interstate highways, in parks, and on university campuses.	59
Figure 30. V_d for horizontal component of man-made noise versus V_d for vertical component.	60
Figure 31. Correlation of V_d and L_d for man-made noise.	61
Figure 32. Lack of correlation of F_a and V_d for man-made noise.	62
Figure 33. Amplitude probability distribution of envelope of man-made radio noise at 48 MHz.	67
Figure 34. Amplitude probability distribution of man-made noise at 102 MHz.	68
Figure 35. Amplitude probability distribution of man-made noise at 102 MHz.	69
Figure 36. Amplitude probability distribution of man-made noise at 102 MHz.	70
Figure 37. Amplitude probability distribution of man-made noise at 48 MHz, 10 kHz bandwidth.	71
Figure 38. Randomly selected 200 ms sample of noise envelope from a 6-minute, 250 MHz central Colorado Springs recording.	
Figure 39. Normalized autocovariance for the noise sample of figure 38.	73
Figure 40. Amplitude probability distribution for a 6-minute sample of noise recorded in central Colorado Springs.	74
Figure 41. Average positive crossing rate characteristic for the sample of noise of figure 40.	75
Figure 42. Pulse duration distributions for the sample of noise of figure 40.	76

Figure 43. Pulse spacing distributions for the sample of noise of figure 40.	77
Figure 44. Randomly selected 200 ms sample of noise envelope from a 6-minute 48 MHz, Denver, Colorado, residential area.	78
Figure 45. Normalized autocovariance for the noise sample of figure 44.	79
Figure 46. Randomly selected 200 ms sample of noise envelope from a 6-minute, 48 MHz, Denver, Colorado, residential area.	80
Figure 47. Normalized autocovariance for the noise sample of figure 46.	81
Figure 48. Amplitude probability distribution for a 6-minute sample of noise recorded in a residential area of Denver, Colorado.	82
Figure 49. Average positive crossing rate characteristic for the sample of noise of figure 48.	83
Figure 50. Pulse duration distributions for the sample of noise of figure 48.	84
Figure 51. Pulse spacing distributions for the sample of noise of figure 48.	85
Figure 52. Comparison of present estimates with JTAC (1968) estimates.	98
Figure A1. Block diagram of the measuring and recording facilities in the OT/ITS mobile radio noise lab.	A13
Figure A2. Block diagram of the analog-recording-playback system.	A14
Figure A3. Block diagram of the correlation measurement system.	A15
Figure A4. OT/ITS mobile radio-noise lab system noise factors.	A16

- Figure B1. Regression of 5.0 MHz $F_{a\mu}$ with log population density of SLA's. B12
- Figure B2. Linear regression of $F_{a\mu}$ vs. log hourly traffic count along 26 thoroughfares at 48 MHz. B12
- Figure B3. Correlation coefficients along with the 95 percent confidence limits for each of measurement frequencies, $F_{a\mu}$ vs. log hourly traffic count. B13
- Figure B4. Hourly median values of radio noise power and hourly traffic count. Broadway, Boulder, Colorado, October 25-27, 1967, noise values recorded 100 ft west of highway center. B14
- Figure B5. Distribution of radio noise power at 20 MHz radiated from 958 individual vehicles, values measured at 50 ft from vehicle. B15
- Figure B6. Distribution of radio noise power at 48 MHz radiated from 958 individual vehicles, values measured at 50 ft from vehicle. B15

LIST OF TABLES

	Page
Table 1. Expected Variation of Median Values about Estimates for Business, Residential, and Rural Locations.	15
Table 2. Expected Variation, Man-Made Radio Noise Levels, about the Median Value for a Location, within the Hour.	17
Table 3. Variation of the Median Value of V_d and L_d with Location for a Given Frequency and Bandwidth.	45

