CONTENTS

Page

ABSTRACT 1

1. INTRODUCTION 1

2. EXPRESSIONS FOR RADIATION IN FREE SPACE OVER GROUND 3
   2.1. Sommerfeld Formulation 4
      2.1.1. Vertical Electric Dipole (VED) 5
      2.1.2. Horizontal Electric Dipole (HED) 6
   2.2. Geometric Optics and Norton Surface-Wave Approximation 7
      2.2.1. Vertical Electric Dipole (VED) 8
      2.2.2. Horizontal Electric Dipole (HED) 8
      2.2.3. Fresnel Reflection Coefficients 9

3. NUMERICAL INTEGRATION TECHNIQUES 10
   3.1. Romberg Quadrature 10
   3.2. Weighted-Averages Method 11
   3.3. Numerical Evaluation of $2Q/k_0^2$, U, V, and W 12

4. FREQUENCY-DOMAIN RESULTS 16
   4.1. Conductivity Variation to Demonstrate Two-Ray Behavior 16
   4.2. Position Variation to Isolate Near-Surface and Near-Field Effects 17
      4.2.1. Surface Wave 21
      4.2.2. Pseudo-Lateral Wave 21
      4.2.3. Near-Field Effects on the Direct Ray 23
   4.3. Contour Plots to Observe Two-Ray Behavior 23

5. TIME-DOMAIN ANALYSIS 24
   5.1. Windowing Techniques to Optimize Pulse Shape 25
   5.2. Practical Bandwidth Limitations 26

6. TIME-DOMAIN RESULTS 27
   6.1. Impulse Responses for Wideband Signals Centered at 900 MHz 27
   6.2. Impulse Responses for Wideband Signals Centered at 2.4 GHz and 5.8 GHz 31
   6.3. Delay Spread Versus Bandwidth and Carrier Frequency 32

7. CONCLUSION 32

8. ACKNOWLEDGMENTS 40

9. REFERENCES 41

APPENDIX A: FIELD STRENGTH VERSUS FREQUENCY AND SEPARATION 47

APPENDIX B: IMPULSE RESPONSES FOR SIGNALS CENTERED AT 2.4 GHz 53

APPENDIX C: IMPULSE RESPONSES FOR SIGNALS CENTERED AT 5.8 GHz 57

APPENDIX D: DELAY SPREAD VERSUS BANDWIDTH 61